

# SMALL SELF-PROPELLED SCISSORLIFT PLATFORM



Official website: <https://www.homsunlift.com>

WhatsApp/Wechat ID: +8613680275183

Email: [sandy519@foxmail.com](mailto:sandy519@foxmail.com)

## 小全自行剪叉式升降平台

SMALL SELF-PROPELLED SCISSORLIFT PLATFORM



	GTJZ-4	GTJZ-6
Safe working load (kg)	230	230
Extended platform safe working load (kg)	113	113
Maximum working height (m)	6	8
Maximum platform height (m)	4	6
Work platform dimensions (length *width*height)	1.3*0.68*1.1	1.68*0.78*1.1
Work platform dimensions (length *width*height)	1.44*0.7*1.46	1.82*0.78*1.62
Overall dimensions of the complete machine (length * width * height, without folding the guardrail)	1.44*0.7*1.86	1.82*0.78*2.02
Platform extension dimension (m)	0.55	0.9
Minimum ground clearance (m) (in retracted state)	0.29	0.29
Minimum ground clearance (M) (raised state)	0.0106	0.0106
Wheelbase (M)	1.02	1.357
Minimum turning radius (M) (inner wheel/outer wheel)	0/1.5	0/2
Lift motor/drive motor (KW)	1.2/0.5KW	1.2/0.5KW
Machine travel speed (km/h) (retracted state)	3.5km/h	3.5km/h
Machine travel speed (km/h) (unclosed state)	0.8	0.8
Rising/falling speed (sec)	95/80	95/80
Battery (V/Ah)	2*12v/80Ah	4*6v/200Ah
Charger (V/A)	24v/30A	24v/30A
Maximum climbing ability (%)	20	20
Maximum allowable working angle (indoor/outdoor)	1.5/3°	1.5/3°
Tire (mm)	230*80	305*100
Whole machine weight (kg)	860kg	1200kg



※工厂保留对用料和技术参数的修改权，请在下单前确认。

The factory reserves the amending right for the materials  
And technical specifications