

Fully self-propelled universal wheel aluminum alloy lifting platform

Official website: <https://www.homsunlift.com>

WhatsApp/Wechat ID: +8613680275183

Email: sandy519@foxmail.com

(标准款)



全自行万向轮铝合金升降平台
FULLY AUTOMATIC HYDRAULIC STEERING
ALUMINUM ALLOY ELEVATING PLATFORM



Load kg	125	125	125	200	200	200
Platform Height mm	4000	5000	6000	4000	5000	6000
Operation Height mm	6000	7000	8000	6000	7000	8000
Work Platform Size (Long × Wide × Distance) mm	600*600	600*600	600*600	1000*600	1000*600	1000*600
Overall dimensions of the device (Long × Wide × Height) mm	1530*760*1750	1530*760*1750	1530*760*1750	1700*1000*1750	1700*1000*1750	1700*1000*1750
Minimum ground clearance mm	45	45	45	45	45	45
Front-to-rear wheelbase mm	1290	1290	1290	1460	1460	1460
Minimum turning radius mm	1530	1530	1530	1700	1700	1700
Heating motor/Driver motor kW	0.8kw/0.5kw	0.8kw/0.5kw	0.8kw/0.5kw	1.2kw/0.5kw	1.2kw/0.5kw	1.2kw/0.5kw
Machine travel speed kw/h (folded state)	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Machine travel speed kW / h (raised state)	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Rise/Fall Speed (sec)	95/80	95/80	95/80	95/80	95/80	95/80
Battery	2*12v/100ah	2*12v/100ah	2*12v/100ah	2*12v/100ah	2*12v/100ah	2*12v/100ah
Charger	24v/10a	24v/10a	24v/10a	24v/10a	24v/10a	24v/10a
Maximum climbing capability %	25	25	25	25	25	25
Maximum allowable working angle (Indoor / Outdoor)	1.5° /1.5°	1.5° /1.5°	1.5° /1.5°	1.5° /1.5°	1.5° /1.5°	1.5° /1.5°
Tyre mm	230×80	230×80	230×80	230×80	230×80	230×80
Total weight kg	450	800	850	800	900	1000