

1.6T Lithium Battery Explosion-proof Forklift Product Model and Parameters

Item	Unit	Parameter	Item	Unit	Parameter
Application site		Zone1, 2, 21, 22	Maximum Travel Speed (Unloaded)	km/h	16
Explosion-proof Rating of Whole Machine		II B T4 Gb/IIIB T4	Lifting Speed (Unloaded)	mm/s	500
Rated Lifting Capacity	kg	1600	Lifting Speed (Unloaded)	mm/s	550
Load Center Distance	mm	500	Maximum Climbing Gradient	%	20
Maximum Lifting Height	mm	3000	Wheelbase	mm	1360
Free Lifting Height	mm	120	Wheel Track (Front/Rear)	mm	890/190
Fork Length	mm	1000	Minimum Ground Clearance	mm	95
Mast Tilt Angle (Forward/Backward)		5/7	Motor Power (Travel/Lifting)	kw	10/16
Overall Dimension	mm	1935x1050x2050	Front/Rear Tire Model (Anti-static)		6.50-10 Anti-static/5.00-8
Minimum Turning Radius	mm	1570	Battery Pack	V/A.H	80/280
Maximum Travel Speed (Loaded)	Km/h	16	Self-weight	kg	3100

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com