

2.0T Lithium Battery Explosion-proof Forklift Product Model and Parameters

Item	Unit	Parameter	Item	Unit	Parameter
Application site		Zone1, 2, 21, 22	Maximum Travel Speed (Unloaded)	km/h	20
Explosion-proof Rating of Whole Machine		II B T4 Gb/IIIB T4	Lifting Speed (Unloaded)	mm/s	420
Rated Lifting Capacity	kg	2000	Lifting Speed (Unloaded)	mm/s	450
Load Center Distance	mm	500	Maximum Climbing Gradient	%	15
Maximum Lifting Height	mm	3000	Wheelbase	mm	1505
Free Lifting Height	mm	140	Wheel Track (Front/Rear)	mm	970/955
Fork Length	mm	1070	Minimum Ground Clearance	mm	105
Mast Tilt Angle (Forward/Backward)		5/8	Motor Power (Travel/Lifting)	kw	16/20.7
Overall Dimension	mm	2305x1195x2195	Front/Rear Tire Model (Anti-static)		7.00-12Anti-static/18x7-8
Minimum Turning Radius	mm	2020	Battery Pack	V/A.H	80/280
Maximum Travel Speed (Loaded)	Km/h	20	Self-weight	kg	3600

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com