

Explosion proof battery forklift 1.5t Product Model and Parameters

Item	Unit	Parameter	Item	Unit	Parameter
Application site		Zone1, 2, 21, 22	Maximum Travel Speed (Unloaded)	km/h	13
Explosion-proof Rating of Whole Machine		II B T4 Gb/IIIB T4	Lifting Speed (Unloaded)	mm/s	310
Rated Lifting Capacity	kg	1500	Lifting Speed (Unloaded)	mm/s	440
Load Center Distance	mm	500	Maximum Climbing Gradient	%	15
Maximum Lifting Height	mm	3000	Wheelbase	mm	1380
Free Lifting Height	mm	135	Wheel Track (Front/Rear)	mm	890/920
Fork Length	mm	920	Minimum Ground Clearance	mm	110
Mast Tilt Angle (Forward/Backward)			Motor Power (Travel/Lifting)	kw	7/8
Overall Dimension	mm	2140x1080x2130	Front/Rear Tire Model (Anti-static)		6.50-10 Anti-static/5.00-8
Minimum Turning Radius	mm	1950	Battery Pack	V/A.H	48/440
Maximum Travel Speed (Loaded)	Km/h	13	Self-weight	kg	2950

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com