

Scissor-type Electric Stacke Product parameters

Specifications Unit		CQD20
Operation Type		Walk-behind
Rated Load Capacity	kg	2000
Load Center Distance	mm	600
Wheelbase	mm	1415
Self-weight	kg	2600
Wheel Material		Polyurethane Wheel/PU
Drive Wheel	mm	φ250x70
Load-bearing Wheel	mm	φ150x100
Inner Width of Outriggers	mm	1200
Tilt Angle of Fork	°	3.5/2.5
Minimum Height after Mast Lowering	mm	2100
Free Lift Height	mm	1520
Lift Height	mm	4500
Height when Fork is Lowered	mm	45
Overall Length	mm	2140
Vehicle Width	mm	1500
Fork Size	mm	35/100/1070
Outer Width of Fork	mm	815
Forward Reach Distance	mm	590
Minimum Ground Clearance of Vehicle Body	mm	56
Aisle Width for 800X1200 Pallet Placed Along Fork	mm	2200
Turning Radius	mm	1460
Overall Length (Excluding Fork)	mm	1670
Travel Speed (Loaded/Unloaded)	Mm/s	3.5/4
Lift Speed (Loaded/Unloaded)	Mm/s	100/200
Lowering Speed (Loaded/Unloaded)	Mm/s	200/100
Maximum Climbing Gradient (Loaded/Unloaded)	%	6/10
Service Brake		Electromagnetic Brake(E/M)
Drive Motor Power	kw	2.2
Lift Motor Power	kw	4.5

Lithium Battery Voltage/Capacity	V/Ah	24V/200Ah
Noise Level at Driver's Ear dB(A)	Db(a)	<70

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com