

Product parameters of mobile boarding bridge

Model	Load (T)	Platform Dimensions (M)						Work Height (M)	
		Slope	Platform	Tailboard	Ramp	Guardrail Height	Platform Width	Minimum Height	Maximum Height
DCQY8T-10M	8	6	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY10T-11M	10	7	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY10T-12M	10	8	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY11T-11M	11	7	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY11T-12M	11	8	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY12T-11M	12	7	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY12T-12M	12	8	3	0.9	0.4	0.26	2.2	1.2	1.68
DCQY15T-10M	15	6	3	0.9	0.4	0.26	Customiz ed	1.2	1.68
DCQY20T-12M	20	8	3	0.9	0.4	0.26	Customiz ed	1.2	1.68
DCQY30T-12M	30	8	3	0.9	0.4	0.26	Customiz ed	1.2	1.68

*(Forklift rated load + forklift self-weight) ×1.4 dynamic load coefficient ≤ platform rated load

*Special specifications can be customized according to your site requirements

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com