

Performance parameters of aluminum alloy elevator

give birth to article Name From:	model	terrace maximum altitude (m)	Rated Load Hole (kg)	Platform Size (m)	supply voltage (V)	power (kw)	Total weight of the machine measure (kg)	outline dimension (m)
Single pillar	GTWY4-100-1	4	150	0.65*0.65	220v	0.75	300	1420*780*1980
	GTWY6-100-1	6	150	0.65*0.65	220v	0.75	320	1420*780*1980
	GTWY8-100-1	8	130	0.65*0.65	220v	0.75	340	1420*780*1980
	GTWY10-100-1	10	130	0.65*0.65	220v	0.75	390	1420*780*1980
Double pillar	GTWY6-200-2	6	300	1.2*0.63	220v	1.1	504	1510*850*2000
	GTWY8-200-2	8	300	1.2*0.63	220v	1.5	580	1510*850*2000
	GTWY10-200-2	10	250	1.5*0.63	220v	1.5	660	1800*850*1990
	GTWY12-200-2	12	250	1.5*0.63	220v	1.5	700	1800*850*1990
	GTWY14-200-2	14	150	1.5*0.63	220v	1.5	870	1940*1050*2350
3 pillar	GTWY12-250-3	12	200	1.57*0.9	220/380	2.2	900	2100*1250*2000
	GTWY14-200-3	14	200	1.57*0.9	220/380	2.2	1000	2100*1250*2350
	GTWY16-200-3	16	200	1.57*0.9	220/380	2.2	1000	2100*1250*2650
4 pillar	GTWY12-250-4	12	200	1.57*0.9	220/380	2.2	1300	2100*1250*2000
	GTWY14-200-4	14	200	1.57*0.9	220/380	2.2	1300	2100*1250*2350
	GTWY16-200-4	16	200	1.57*0.9	220/380	2.2	1500	2100*1250*2650
	GTWY18-250-4	18	200	1.57*0.9	220/380	2.2	1700	2100*1350*2900
Special Purchase Notice								
DC single-column product (with 2 batteries; capacity: 60 AH) + Price: 2000 yuan								
DC double-column product (with 2 batteries, capacity: 80 AH) + Price: 2500 yuan								
Dual-purpose single-column battery pack (2 batteries, 60 Ah) + RMB 4,000								
Dual-purpose dual-column battery pack (2 batteries, 80 AH capacity) + RMB 4,500								
Assisted walking single-column product (2 batteries, 60 Ah) + RMB 8,500								
Assisted Walking Dual-Pole Product (2 batteries, 80 AH) + RMB 9,000								

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com