

Product parameters of fully electric station driven pallet stacker truck

Overview To	Model/Configuration Number	/	CDD15-WH	CDD20-WH
	mode of operation	/	Station-type	Station-type
	rated load weight	Q (kg)	1500	2000
	Load center distance	c(mm)	600	600
	wheel base	y(mm)	1150	1290
weight	Total weight of the device (including battery)	kg	675	860
Car wheel And wheel foetus	tyre type	/	polyurethane	Polyurethane
	Drive Wheel Size/Number	mm	210×75/1	250×80/1
	Load-bearing wheel size/number	mm	80×70/4	80×70/4
	Auxiliary Wheel Size/Number	mm	115×55/2	115×55/2
	Wheelbase-Front	b10(mm)	655	655
	Wheelbase – Rear	b11(mm)	510	510
Height Cun	lifting altitude	h3(mm)	3000	3000
	Minimum fork height	h13(mm)	90	90
	Total Length	L1(mm)	1865	2000
	total width	b1(mm)	820	820
	Fork Size	sXeXL(mm)	60×170×1150	60×170×1150
	Fork outer width	b5(m)	680	680
	Minimum ground clearance	m2(mm)	30	30
	Minimum right-angle stacking channel width: 1000 × 1200 (1200 span for forklifts)	Ast (mm)	2070	2215
	Minimum right-angle stacking channel width: 800×1200 (with 1200 along the forklift arm)	Ast(mm)	2120	2265
	minimum turning radius	Wa(mm)	1420	1565
nature Can	Speed: Full Load / Empty Load	km/b	3.8/4.2	4.5/5.0
	Lifting Speed (Full Load/No Load)	mm/s	85/135	75/135
	Descent Rate (Full Load/No Load)	mm/s	120/120	120/120

	Maximum slope: Full load / Empty load	%	3/6	5/10
electricity machine And electricity Pool	Power of the driving motor	kW	0.75	1.5
	Lifting motor power	kW	2.2	2.2
	Battery Pack Voltage/Capacity	V/Ah	24/90	24/120
other	controller	/	direct-current	exchange
Frame Selection Parameters				
rated load weight	specifications and models Gantry lifting height	Truss Recess Height	Roof truss extension height	Maximum load capacity at the highest point (Payload center distance: 600)
kg	mm	mm	mm	kg
1500	2000	1495	2495	1500
	2500	1745	2995	1500
	3000	1995	3495	1000
	3500	2245	3995	600
2000	2000	1495	2495	2000
	2500	1745	2995	2000
	3000	1995	3495	1200
	3500	2245	3995	800

*We are the [source manufacturer](#) and can also customize various types of forklifts according to customer needs.

*If needed, you can consult customer service.

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com