

T30 Off-road Forklift Parameter Table			
engine	All-Wheel Drive 490	tyre	20.5/70-16
Maximum Load Capacity	3000KG	Fork Length (Standard)	1220MM
Center-to-ground clearance of the wheelbase	200MM	Frame ingot connection	First 30 mm; Next 20 mm
axle	Edge of the cast steel small wheel	Driving Method	All-Wheel Drive
gear-box	265 Overall Torque Converter	Total weight of the device	3360KG
turning radius	2400MM	Ground clearance of the front section of the gantry	170-250MM
Gantry width	1600MM	External Dimensions	4000*1800*2700
Lifting Height (Standard)	3000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T35 Off-road Forklift Parameter Table			
engine	All-Wheel Drive 490	tyre	20.5/70-16
Maximum Load Capacity	3500KG	Fork Length (Standard)	1220MM
Center-to-ground clearance of the wheelbase	200MM	Frame ingot connection	First 30 mm; Next 20 mm
axle	Edge of the cast steel small wheel	Driving Method	All-Wheel Drive
gear-box	265 Overall Torque Converter	Total weight of the device	3360KG
turning radius	2400MM	Ground clearance of the front section of the gantry	170-250MM
Gantry width	1600MM	External Dimensions	4000*1800*2700
Lifting Height (Standard)	3000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T35 Forklift Model: Off-road Forklift Parameter Table			
engine	All-Wheel Drive 490	tyre	23.5/70-16
Maximum Load Capacity	3500KG	Fork Length (Standard)	1220MM
Center-to-ground clearance of the wheelbase	300MM	Frame ingot connection	First 30 mm; Next 20 mm
axle	Edge of the cast steel small wheel	Driving Method	All-Wheel Drive
gear-box	265 Overall Torque Converter	Total weight of the device	3420KG
turning radius	2400MM	Ground clearance of the front section of the gantry	170-250MM
Gantry width	1600MM	External Dimensions	3800*1800*2200
Lifting Height (Standard)	3000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T35 Off-road Forklift Parameter Table			
engine	All-Wheel Drive 490	tyre	23.5/70-16
Maximum Load Capacity	3500KG	Fork Length (Standard)	1220MM
Center-to-ground clearance of the wheelbase	300MM	Frame ingot connection	First 30 mm; Next 20 mm
axle	Edge of the cast steel small wheel	Driving Method	All-Wheel Drive
gear-box	265 Overall Torque Converter	Total weight of the device	3360KG
turning radius	2400MM	Ground clearance of the front section of the gantry	170-250MM
Gantry width	1600MM	External Dimensions	3800*1800*2200
Lifting Height (Standard)	3000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T40 Off-road Forklift Parameter Table			
engine	Four-wheel drive 4102 turbocharged	tyre	16/70-16
Maximum Load Capacity	5000KG	Fork Length (Standard)	1520MM
Center-to-ground clearance of the wheelbase	350MM	Frame ingot connection	Front: 40 mm; Rear: 30 mm
axle	Edge of the large cast steel wheel	Driving Method	All-Wheel Drive
gear-box	280 Overall Torque Converter	Total weight of the device	4580KG
turning radius	3250MM	Ground clearance of the front section of the gantry	300-380MM
Gantry width	1800MM	External Dimensions	4450*2000*2800
Lifting Height (Standard)	4000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T50 Off-road Forklift Parameter Table			
engine	Four-wheel drive 4102 turbocharged	tyre	16/70-20
Maximum Load Capacity	5000KG	Fork Length (Standard)	1520MM
Center-to-ground clearance of the wheelbase	350MM	Frame ingot connection	Front: 40 mm; Rear: 30 mm
axle	Edge of the large cast steel wheel	Driving Method	All-Wheel Drive
gear-box	280 Overall Torque Converter	Total weight of the device	4580KG
turning radius	3250MM	Ground clearance of the front section of the gantry	300-380MM
Gantry width	1800MM	External Dimensions	4450*2000*2800
Lifting Height (Standard)	4000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

T70 Off-road Forklift Parameter Table			
engine	Four-wheel drive 4102 turbocharged	tyre	Four steel wires at the front and two at the rear; a steel wire tire.
Maximum Load Capacity	7000KG	Fork Length (Standard)	1520MM
Center-to-ground clearance of the wheelbase	450MM	Frame ingot connection	First 40 mm; Second 30 mm
axle	28. Enhanced cast steel bridge	Driving Method	All-Wheel Drive
gear-box	280 Overall Torque Converter	Total weight of the device	6800KG
turning radius	3250MM	Ground clearance of the front section of the gantry	300-380MM
Gantry width	2000MM	External Dimensions	5000*2400*2800
Lifting Height (Standard)	4000MM	Forward tilt angle	6/12
Hill Descent Angle	38%	manufacturer	Homsunlift.com
Hand measurement may contain errors; please refer to the actual measurement for accurate results.			

*We are the [source manufacturer](#) and can also customize various types of forklifts according to customer needs.

*If needed, you can consult customer service.

Official website:<https://www.homsunlift.com>

WhatsApp/Wechat ID:+8613680275183

Email:sandy519@foxmail.com

Related product recommendations:

[Lithium Battery Counterbalanced Forklift](#)

[Fuel-powered Counterbalance Forklift](#)

[Internal Combustion Explosion-proof Forklift 3.5T](#)

[Electric Handling Truck for Off-Road Use](#)

[off-road electric pallet truck](#)